

## CLAIMS

What is claimed is:

- 1           1. A cylindrical wear resistant band for providing a wear protection  
2 surface over an inside surface of a cylindrical member in a rock crusher, the  
3 cylindrical wear resistant band comprising:  
4           a cast piece including a plurality of curvilinear segments, the  
5 curvilinear segments being separated from each other by a portion of reduced  
6 thickness, whereby the portion of reduced thickness can be cut through to separate  
7 the curvilinear segments after installation on the inside surface of the cylindrical  
8 member in the rock crusher.
- 1           2. The cylindrical wear resistant band of claim 1, wherein the  
2 curvilinear segments are formed of a ceramic material.
- 1           3. The cylindrical wear resistant band of claim 1, wherein the  
2 curvilinear segments are formed of materials containing iron.
- 1           4. The cylindrical wear resistant band of claim 2, wherein the cast  
2 piece forms an arc of 360 degrees.
- 1           5. The cylindrical wear resistant band of claim 1, wherein the cast  
2 piece forms an arc of at least 180 degrees.
- 1           6. The cylindrical wear resistant band of claim 1 wherein the cast  
2 piece forms an arc of at least 90 degrees.
- 1           7. The cylindrical wear resistant band of claim 1, wherein the  
2 cylindrical member is configured as a concave for a gyratory crusher, and the cast  
3 piece includes at least three curvilinear segments.

09758680 041301

1           8. The cylindrical wear resistant band of claim 1, wherein the  
2 portion of reduced thickness is a groove having a depth of less than an average  
3 thickness from an inside surface of the cast piece to an outside surface of the cast  
4 piece.

1           9 In a rock crusher including a wear protection arrangement for a  
2 surface to protect the surface from wear, the surface supporting a crushing operation  
3 of the rock crusher, the wear protection arrangement comprising:  
4           a plurality of curvilinear segments connected by a portion of reduced  
5 thickness.

1           10. The wear protection arrangement of claim 9, wherein the  
2 segments are formed of a metal material.

1           11. The wear protection arrangement of claim 9, wherein the  
2 portions of reduced thickness are vertical with respect to the rock crusher.

1           12. The wear protection arrangement of claim 9, wherein the  
2 curvilinear segments are comprised of at least three segments and two of the  
3 segments are connected by the portion of reduced thickness and a third of the  
4 segments is connected to one of the two segments by another portion of reduced  
5 thickness.

1           13. A method of repairing or manufacturing a rock crusher having a  
2 shell, the shell being exposed to wear when the rock crusher is operational, the  
3 method comprising step of:  
4           attaching a one piece wear band including segments separated by a  
5 portion of reduced thickness to the shell.

09758680 "041301

1 14. The method of claim 13, further comprising the step of:  
2 cutting the wear band at the portion of reduced thickness.

1 15. The method of claim 14, wherein the cutting step includes  
2 mechanically cutting or cutting with heat.

1 16. A concave for a gyratory crusher, the gyratory crusher including  
2 a shell and a spider, the shell having a concave surface, the shell and the spider  
3 defining a recess, the concave comprising:

4 a top end having a flange, the flange being configured to be received  
5 in the recess.

1 17. The concave of claim 16, further comprising:  
2 a lip extending above the flange.

1 18. The concave of claim 17, wherein the lip has an inside surface  
2 continuous with an inside surface of the concave.

1 19. The concave of claim 16, wherein the flange includes at least one  
2 aperture.

1 20. The concave of claim 16, wherein the concave is an annular  
2 ring.

1 21. A gyratory crusher, comprising:  
2 a shell;  
3 a spider disposed over the shell, the shell and the spider defining a  
4 recess; and

5 a concave covering at least a portion of the shell, the concave  
6 including a top end having a flange, the flange being configured to be received in  
7 the recess.

1 22. The gyratory crusher of claim 21, further comprising:  
2 a lip extending above the flange.

1 23. A method of repairing or assembling a gyratory rock crusher  
2 including a spider and a shell the method comprising:  
3 placing a concave element on a rim of the shell, the concave element  
4 having a flange and a lip, the flange resting on the rim of the shell; and  
5 disposing the spider over the shell, thereby capturing the flange  
6 between the spider and the rim of the shell.

1 24. The method of claim 23, wherein a gap is defined by the flange  
2 and spider, further comprising:  
3 filling the gap with backing material.

1 25. The method of claim 23, wherein the flange includes an aperture  
2 and further comprising:  
3 pouring backing material through the aperture.

1 26. The method of claim 25, wherein the backing material is poured  
2 after the disposing step.

09758680-044301  
T06T40" 08985260

1                    27. A cylindrical wear resistant band for providing a wear protection  
2 surface over an inside surface of a cylindrical member in a rock crusher, the  
3 cylindrical wear resistant band comprising:  
4                    a cast piece including a plurality of curvilinear segments, the  
5 curvilinear segments capable of being separated from each other, whereby the band  
6 can be cut to separate the curvilinear segments after installation on the inside surface  
7 of the cylindrical member in the rock crusher.

1                    28. The cylindrical wear resistant band of claim 27, further  
2 comprising:  
3                    portions of reduced thickness separating the curvilinear segments.

00758680 041301  
T0E740" 08985260